




# MICRO

## CARATTERISTICHE TECNICHE



- Pressione max. d'esercizio 6 bar
- Temperatura min/max. d'esercizio da 0°C a +40°C
- Testata in ABS
- Vaso in SAN trasparente
- Attacchi filettati da 3/4" M/F
- Cartuccia in rete

## TECHNICAL FEATURES

- Max. working pressure 6 bar
- Min/max. working temperature 0°C / +40°C
- ABS head
- Transparent SAN bowl
- Threaded connections 3/4" M/F
- Cartridge washable net

### CONTENITORE ADATTO AD USO TECNICO PER FILTRAZIONE IN LINEA.

HOUSING FOR TECHNICAL APPLICATIONS - A PRACTICAL ITEM THAT OFFERS LARGE VERSATILITY OF USE.

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT
0AR030310	M/F 3/4»	5" MINI	60 - 125	4000	24	3,5	0,34

P.S.C MASTER



24 pz. 28\*41\*14 alveare

**\*CARTUCCE CONSIGLATE**  
**RECOMMENDED USABLE CARTRIDGES**  
GT MICRO  
RIF. PAG. 5