

# OP602.si



CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.

HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.

## CARATTERISTICHE TECNICHE


- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Testata in polipropilene caricato
- Staffabile

## TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature 0°C / +40°C
- Head made of filled polypropylene
- Possibility to equip with wall bracket

## CON VASO IN POLIPROPILENE BIANCO / WITH WHITE POLYPROPYLENE BOWL

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITA	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A2050140	1/4"	5"	133 - 195	1500	24	20	0,83	0,112
0A2050240	3/8"	5"	133 - 195	5000	24	20	0,83	0,112
0A2050340	1/2"	5"	133 - 195	6000	24	20	0,83	0,112
0A2050440	3/4"	5"	133 - 195	6500	24	20	0,83	0,112
0A2050540	1"	5"	133 - 195	7000	24	20	0,83	0,112
0A2070140	1/4"	7"	133 - 245	1500	12	11	0,92	0,091
0A2070240	3/8"	7"	133 - 245	5000	12	11	0,92	0,091
0A2070340	1/2"	7"	133 - 245	6000	12	11	0,92	0,091
0A2070440	3/4"	7"	133 - 245	6500	12	11	0,92	0,091
0A2070540	1"	7"	133 - 245	7000	12	11	0,92	0,091
0A2090140	1/4"	9 3/4"	133 - 307	1500	12	12	1,00	0,091
0A2090240	3/8"	9 3/4"	133 - 307	5000	12	12	1,00	0,091
0A2090340	1/2"	9 3/4"	133 - 307	6000	12	12	1,00	0,091
0A2090440	3/4"	9 3/4"	133 - 307	6500	12	12	1,00	0,091
0A2090540	1"	9 3/4"	133 - 307	7000	12	12	1,00	0,091



P.S.C MASTER

CONFEZIONE / PACKAGING



5" = 24 pz. 44\*57\*44  
7" - 93/4" = 12 pz. 46\*58\*37



1pz. 14\*14\*21  
1pz. 14\*14\*33

\*CARTUCCE CONSIGLIATE

RECOMMENDED USABLE CARTRIDGES

FA/PA/FA/CA/ GTS\*/GTSX\*/FPP/GT-GTL/CE/GTX  
RIF. PAG.