



OP803.ci

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Inserti in ottone
- Testata in polipropilene caricato
- Staffabile

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Min/max. working temperature 0°C / +40°C
- Brass inserts
- Head made of filled polypropylene
- Possibility to equip with wall bracket


CON VASO IN SAN TRASPARENTE / WITH TRANSPARENT SAN BOWL

CON VASO IN POLIPROPILENE BIANCO / WITH WHITE POLYPROPYLENE BOWL

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITÀ	VOL. M3
CODE	CONNECT.	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT	VOL. M3
0A8203341	1/2"	20"	133 - 588	6000	6	12	2.00	0.11
0A8203441	3/4"	20"	133 - 588	6500	6	13	2.17	0.11
0A8203541	1"	20"	133 - 588	7000	6	13	2.17	0.11
0A8203641	1 1/4" *	20"	133 - 588	13000	6	12	2.00	0.11
0A8203741	1 1/2" *	20"	133 - 588	13000	6	12	2.00	0.11
0A8053341	1/2"	5"	133 - 195	6000	24	20	0.83	0.112
0A8053441	3/4"	5"	133 - 195	6500	24	20	0.83	0.112
0A8053541	1"	5"	133 - 195	7000	24	20	0.83	0.112
0A8053641	1 1/4" *	5"	133 - 195	13000	24	20	0.83	0.112
0A8053741	1 1/2" *	5"	133 - 195	13000	24	20	0.83	0.112
0A8073341	1/2"	7"	133 - 245	6000	12	11	0.92	0.091
0A8073441	3/4"	7"	133 - 245	6500	12	11	0.92	0.091
0A8073541	1"	7"	133 - 245	7000	12	11	0.92	0.091
0A8073641	1 1/4" *	7"	133 - 245	13000	12	11	0.92	0.091
0A8073741	1 1/2" *	7"	133 - 245	13000	12	11	0.92	0.091
0A8093341	1/2"	9 3/4"	133 - 307	6000	12	12	1.00	0.091
0A8093441	3/4"	9 3/4"	133 - 307	6500	12	12	1.00	0.091
0A8093541	1"	9 3/4"	133 - 307	7000	12	12	1.00	0.091
0A8093641	1 1/4" *	9 3/4"	133 - 307	13000	12	12	1.00	0.091
0A8093741	1 1/2" *	9 3/4"	133 - 307	13000	12	12	1.00	0.091

CONTENITORE AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO.

HOUSING FOR DOMESTIC AND TECHNOLOGICAL USES FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.



P.SC MASTER	CONFEZIONE / PACKAGING
-------------	------------------------



5" = 24 pz. 44*57*44
7" - 9 3/4" = 12 pz. 46*58*37
20" = 6 pz. 51*62*40



1pz. 14*14*21
1pz. 14*14*33
1pz. 18*60*15

***CARTUCCE CONSIGLIATE**

RECOMMENDED USABLE CARTRIDGES

FA/PA/FA/CA/GTS*/GTSX*/FPP/GT-GTL/CE/GTX
RIF. PAG.