

FILTRO ANTICALCARE MULTIUSO / MULTIUSE SCALE REDUCTION FILTER

FILTRO AD USO INDUSTRIALE PER LA DOSATURA DI POLIFOSFATI, APPLICABILE SU CIRCUITI DI PANNELLI SOLARI, CALDAIE, ECC.
INDUSTRIAL FILTER FOR SCALE REDUCTION. SUITABLE FOR PROTECTION OF SOLAR PANNEL CIRCUITS, BOILERS, ETC.



CRISTALSOFT MAX

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 8 bar
- Temperatura d'esercizio da 0°C a +30°C
- Testata e ghiera in polipropilene
- Vaso in SAN trasparente
- Polifosfati in cristalli all'interno

TECHNICAL FEATURES

- Max. working pressure 8 bar
- Working temperature 0°C / +30°C
- Polypropylene head and ring
- Transparent SAN bowl
- Filled with polyphosphate crystals

CODICE	MOD.	DESCRIZIONE	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	KG PER MASTER	KG PER UNITA
CODE	MOD.	DESCRIPTION	CARTR. LENGHT	DIM. L - H MM	FLOW RATE LT/H	PIECES PACKING	KG PER MASTER	KG UNIT
0F1CS4S	SOFT S	con polifosfati/with polyphosphates	M/F 3/4"	60 - 125	500	24	6	0,25
0F1CS4S00B	SOFT B	con polifosfati blisterato/blistered with polyphosphates blistered	M/F 3/4"	60 - 125	500	24	8	0,33
0F1CS4V	SOFT V	vuoto/ empty	M/F 3/4"	60 - 125	500	24	4	0,17

Cod. 3K000110: Confezione kg. 0,175 polifosfati in cristalli.
Cod. 3K000110: Kg. 0,175 package of polyphosphate crystals.

Cod. 3K000111: Confezione kg. 0,500 polifosfati in cristalli.
Cod. 3K000111: Kg. 0,500 package of polyphosphate crystals.



Cod.3K0001105 Kit diffusore per CRISTALSOFT MAX 5"
Cod. 3K0001105 Dispenser kit for CRISTALSOFT MAX 5"

Cod.3K0001107 Kit diffusore per CRISTALSOFT MAX 7"
Cod. 3K0001107 Dispenser kit for CRISTALSOFT MAX 7"

Cod.3K0001109 Kit diffusore per CRISTALSOFT MAX 9" 3/4
Cod. 3K0001109 Dispenser kit for CRISTALSOFT MAX 9" 3/4

