amg water filters

MADE IN ITALY

CONTENITORI PER CARTUCCE SERIE OTTONE E INOX

Brass and inox housings for cartridges




PRODOTTI PER USO DOMESTICO

PRODOTTI PER USO INDUSTRIALE

CONTENITORE AD USO DOMESTICO, TECNOLOGICO, CIVILE E INDUSTRIALE PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON ELEVATI STANDARD DI RESISTENZA MECCANICA E DI DURATA.
HOUSING FOR DOMESTIC, TECHNOLOGICAL, INDUSTRIAL AND CIVIL USE. SUITABLE FOR TREATMENT OF DRINKING WATER IN GENERAL WITH NEUTRAL PH. HIGH STANDARD LEVEL OF MECHANICAL RESISTANCE AND DURABILITY.






SE mini

- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Vaso in SAN trasparente


- *Max. working pressure 8 bar*
- *Min/max. working temperature 0°C / +40°C*
- *Trasparent SAN bowl*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0AM43S21	3/8"	MINI	85 -168	4000	24	20	0,83	0,073
0AM43S31	1/2"	MINI	85 -168	4500	24	20	0,83	0,073

MASTER BOX	CONFEZIONE / *PACKAGING*
	
30 pz. unit. 45*53*33 (cm)	1pz. unit. 10*21*10 (cm)

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES
FA 5" MINI / X/FPP MINI/CV MINIGT MINI/CA MINIGTX MINI/CP MINI
PAG./PG.60 / 70 / 63 / 72 / 72 / 67 / 72





SP mini

- Pressione max. d'esercizio 12 bar
- Temperatura min/max d'esercizio da 0°C a +50°C
- Vaso in POLIAMMIDE


- *Max. working pressure 12 bar*
- *Min/max. working temperature 0°C / +50°C*
- *POLYAMIDE bowl*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0AM43S23	3/8"	MINI	85 -168	4000	24	20	0,83	0,073
0AM43S33	1/2"	MINI	85 -168	4500	24	20	0,83	0,073

MASTER BOX	CONFEZIONE / *PACKAGING*
	
30 pz. unit. 45*53*33 (cm)	1pz. unit. 10*21*10 (cm)

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES
FA 5" MINI / X/FPP MINI/CV MINI/GT MINI/CA MINI/GTX MINI/CP MINI
PAG./PG.60 / 70 / 63 / 72 / 72 / 67 / 72






Sx mini

- Pressione max. d'esercizio 20 bar
- Temperatura min/max d'esercizio da 0°C a +90°C
- Vaso in INOX

- *Max. working pressure 20 bar*
- *Min/max. working temperature 0°C / +90°C*
- *INOX bowl*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0AM34S28	3/8"	4 3/4"	85 -168	4000	24	20	0,83	0,073
0AM34S38	1/2"	4 3/4"	85 -168	4500	24	20	0,83	0,073

MASTER BOX	CONFEZIONE / *PACKAGING*
	
30 pz. unit. 45*53*33 (cm)	1pz. unit. 10*21*10 (cm)

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES
FA 5" MINI / X/FPP MINI/CV MINIGT MINI/CA MINIGTX MINI/CP MINI
PAG./PG.60 / 70 / 63 / 72 / 72 / 67 / 72

CARATTERISTICHE TECNICHE

- Testata 3 vie e ghiera in ottone nichelato
- Selezione orizzontale/verticale con tappo+O Ring inclusi
- Staffabile
- Per cartucce 4" 3/4 MINI (H=122)

TECHNICAL FEATURES

- *Three-ways head and ring made of nickel-plated brass*
- *Selection of horizontal or vertical way-out by means of thread plug with O-ring*
- *Possibility to equip with wall bracket*
- *For cartridges 4" 3/4 MINI (H=122)*



SE600

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 8 bar
- Temperatura min/max d'esercizio da 0°C a +40°C
- Testata e ghiera in ottone nichelato
- Testata con foro M6 per tirante cartuccia nelle versioni 1/2" - 3/4" - 1"
- Predisposizione per manometro
- Vite scarico pressione
- Staffabile nelle versioni con attacchi da 1/2" - 3/4" - 1"

* Testate con attacchi da 1"1/4, 1" 1/2, 2" montano cartucce GTS

TECHNICAL FEATURES

- *Max. working pressure 8 bar*
- *Min/max. working temperature 0°C / +40°C*
- *Nickel plated brass head and ring*
- *1/2", 3/4", 1" heads have M6 hole for cartridge stay-rod*
- *Possibility to equip with pressure gauge*
- *Pressure release screw*
- *The models having 1/2" - 3/4" - 1" connections can be equipped with wall bracket*

** Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS*

CONTENITORE AD USO DOMESTICO, TECNOLOGICO, CIVILE E INDUSTRIALE PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON ELEVATI STANDARD DI RESISTENZA MECCANICA E DI DURATA.


HOUSING FOR DOMESTIC, TECHNOLOGICAL, INDUSTRIAL AND CIVIL USE. SUITABLE FOR TREATMENT OF DRINKING WATER IN GENERAL WITH NEUTRAL PH. HIGH STANDARD LEVEL OF MECHANICAL RESISTANCE AND DURABILITY.

CON VASO IN SAN TRASPARENTE / *WITH TRANSPARENT SAN BOWL*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6090310	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190310	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090410	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190410	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090510	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190510	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100610	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201610	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100710	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200710	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100810	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200810	2" *	19"	135 - 565	14000	6	26	4,33	0,11

SE600 sc





VASO IN SAN TRASPARENTE CON FORO PER SCARICO IN OTTONE DA 1/2"
SAN BOWL WITH 1/2" BRASS WASTE DISCHARGE OUTLET AT THE BOTTOM

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÀ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6090311	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190311	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090411	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190411	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090511	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190511	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100611	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201611	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100711	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200711	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100811	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200811	2" *	19"	135 - 565	14000	6	26	4,33	0,11

MASTER BOX	CONFEZIONE / *PACKAGING*
9 3/4" = 6 pz. unit. 40*40*40 (cm) 19" = 6 pz. unit. 51*62*40 (cm)	1pz. unit. 13*37*18 (cm) 1pz. unit. 18*60*15 (cm)

***CARTUCCE CONSIGLIATE**
RECOMMENDED CARTRIDGES
SE600: FA/FA/PA/CA/FPP/X/GT-GTL/GTX/XP/CA/CP/CV/GTS* /GTSX*/XSM*
PAG./PG.60 / 61 / 72 / 63 / 70 / 64 / 70 / 72 / 66 / 71
SE600 sc: GTX/AP/XSM/GTSX/AP/XM/AP
PAG./PG.67 / 65 / 71 / 67 / 71



SP600

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 12 bar
- Temperatura min/max d'esercizio da 0°C a +50°C
- Testata e ghiera in ottone nichelato
- Testata con foro M6 per tirante cartuccia nelle versioni 1/2" - 3/4" - 1"
- Predisposizione per manometro
- Vite scarico pressione
- Staffabile nelle versioni con attacchi da 1/2" - 3/4" - 1"

*Testate con attacchi da 1"1/4, 1" 1/2, 2" montano cartucce GTS

TECHNICAL FEATURES

- *Max. working pressure 12 bar*
- *Min./max. working temperature 0°C / +50°C*
- *Nickel plated brass head and ring*
- *1/2", 3/4", 1" heads have M6 hole for cartridge stay-rod*
- *Possibility to equip with pressure gauge*
- *Pressure release screw*
- *The models having 1/2" - 3/4" - 1" connections can be equipped with wall bracket*

** Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS*

CONTENITORE AD USO DOMESTICO, TECNOLOGICO, CIVILE E INDUSTRIALE PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON ELEVATI STANDARD DI RESISTENZA MECCANICA E DI DURATA.

HOUSING FOR DOMESTIC, TECHNOLOGICAL, INDUSTRIAL AND CIVIL USE. SUITABLE FOR TREATMENT OF DRINKING WATER IN GENERAL WITH NEUTRAL PH. HIGH STANDARD LEVEL OF MECHANICAL RESISTANCE AND DURABILITY.

VASO IN POLIAMMIDE / *WITH POLYAMIDE BOWL*


CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6090330	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190330	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090430	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190430	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090530	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190530	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100630	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201630	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100730	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200730	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100830	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200830	2" *	19"	135 - 565	14000	6	26	4,33	0,11


SP600 sc



VASO IN POLIAMMIDE CON FORO PER SCARICO IN OTTONE DA 1/2"
POLYAMIDE BOWL WITH 1/2" BRASS WASTE DISCHARGE OUTLET

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6090331	1/2"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190331	1/2"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090431	3/4"	9 3/4"	135 - 337	6000	6	15	2,50	0,064
0A6190431	3/4"	19"	135 - 565	6000	6	19	3,17	0,11
0A6090531	1"	9 3/4"	135 - 337	6300	6	15	2,50	0,064
0A6190531	1"	19"	135 - 565	6300	6	19	3,17	0,11
0A6100631	1 1/4" *	9 3/4"	135 - 337	12000	6	18	3,00	0,064
0A6201631	1 1/4" *	19"	135 - 565	12000	6	21	3,50	0,11
0A6100731	1 1/2" *	9 3/4"	135 - 337	13000	6	18	3,00	0,064
0A6200731	1 1/2" *	19"	135 - 565	13000	6	21	3,50	0,11
0A6100831	2" *	9 3/4"	135 - 337	14000	6	24	4,00	0,064
0A6200831	2" *	19"	135 - 565	14000	6	26	4,33	0,11



MASTER BOX	CONFEZIONE / *PACKAGING*
	
9 3/4" = 6 pz. unit. 40*40*40 (cm) 19" = 6 pz. unit. 51*62*40 (cm)	1pz. unit. 13*37*18 (cm) 1pz. unit. 18*60*15 (cm)

***CARTUCCE CONSIGLIATE**
RECOMMENDED CARTRIDGES
SE600: /FA/FA/PA/CA/FPP/X/GT-GTL/GTX/XP/CA /CP/CV/ GTS* /GTSX* / XSM*
PAG./PG.60 / 61 / 72 / 63 / 70 / 64 / 70 / 72 / 66 / 71
SE600 sc: GTX/AP/XSM/GTSX/AP/XM/AP
PAG./PG.67 / 65 / 71 / 67 / 71

FILTRO AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON BY PASS INTEGRATO.
FILTER WITH INTEGRATED BY PASS FOR DOMESTIC AND TECHNOGICAL USE. SUITABLE FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.




FB

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 12 bar
- Temperatura min/max d'esercizio da 0°C a +50°C
- Testata in ottone nichelato con By-Pass incorporato
- Ghiera in ottone nichelato
- Vaso in poliammide trasparente
- Cartuccia filtrante lavabile da 60µm
- Entrata standard (SX)

TECHNICAL FEATURES

- *Max. working pressure 12 bar*
- *Min./max.working temperature 0°C / +50°C*
- *Nickel plated brass head with integrated By-Pass*
- *Nickel plated brass ring*
- *Transparent polyamide bowl*
- *Equipped with washable filtering cartridge 60µm*
- *Standard inlet (left)*



CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A7091030	1" sx	9 3/4"	117 - 368	4000	6	20	3,33	0,096
0A7191030	1" sx	19"	117 - 618	4000	6	23	3,83	0,096
0A7090030	1" dx	9 3/4"	117 - 368	4000	6	20	3,33	0,096
0A7190030	1" dx	19"	117 - 618	4000	6	23	3,83	0,096

MASTER BOX	CONFEZIONE / *PACKAGING*
	
5 pz. unit. 40*30*30 (cm)	1pz. unit. 22*37*17 (cm) 1pz. unit. 18*60*15 (cm)

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES
FPP / GTX / GT / FA
PAG./PG.63 / 66 / 65 / 60

FILTRO AD USO DOMESTICO E TECNOLOGICO PER IL TRATTAMENTO DI ACQUE POTABILI IN GENERALE A PH NEUTRO, CON BY PASS INTEGRATO.
FILTER WITH INTEGRATED BY PASS FOR DOMESTIC AND TECHNOGICAL USE. SUITABLE FOR TREATMENT OF DRINKING WATER WITH NEUTRAL PH.



COMBI

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 12 bar
- Temperatura min/max d'esercizio da 0°C a +50°C
- Testata e ghiera in ottone nichelato
- Vaso in poliammide trasparente
- Cartuccia filtrante lavabile da 60µm
- Rubinetti di prelievo
- Regolatore durezza
- Entrata standard (SX)

TECHNICAL FEATURES

- *Max. working pressure 12 bar*
- *Min/max. working temperature 0°C / +50°C*
- *Nickel plated brass head and ring*
- *Transparent polyamide bowl*
- *Equipped with washable filtering cartridge 60µm*
- *Draw-off taps*
- *Hardness adjuster*
- *Standard inlet (left)*

VERSIONE CON RACCORDI CURVI 1" / *VERSION WITH 1" CURVED FITTINGS*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A7091130	1" sx	9 3/4"	117 - 428	4000	6	23	3,83	0,096
0A7191130	1" sx	19"	117 - 678	4000	6	26	4,33	0,096
0A7090130	1" dx	9 3/4"	117 - 428	4000	6	23	3,83	0,096
0A7190130	1" dx	19"	117 - 678	4000	6	26	4,33	0,096




VERSIONE CON RACCORDI DRITTI 1" / *VERSION WITH 1" STRAIGHT FITTINGS*

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A7091131	1" sx	9 3/4"	117 - 428	4000	6	23	3,83	0,096
0A7191131	1" sx	19"	117 - 678	4000	6	26	4,33	0,096
0A7090131	1" dx	9 3/4"	117 - 428	4000	6	23	3,83	0,096
0A7190131	1" dx	19"	117 - 678	4000	6	26	4,33	0,096

MASTER BOX	CONFEZIONE / *PACKAGING*
	
5 pz. unit. 40*30*30 (cm)	1pz. unit. 22*37*17 (cm) 1pz. unit. 18*60*15 (cm)

*CARTUCCE CONSIGLIATE
RECOMMENDED CARTRIDGES
FPP / GTX / GT / FA
PAG./PG.63 / 66 /65 / 60





SX600

CARATTERISTICHE TECNICHE

- Pressione max. d'esercizio 15 bar
- Temperatura min/max d'esercizio da 0°C a +90°C
- Testata e ghiera in ottone nichelato
- Testata con foro M6 per tirante cartuccia nelle versioni 1/2" - 3/4" - 1"
- Predisposizione per manometro
- Vite scarico pressione
- Staffabile nelle versioni con attacchi da 1/2" - 3/4" - 1"

* Testate con attacchi da 1"1/4, 1" 1/2, 2" montano cartucce GTSTS

TECHNICAL FEATURES

- *Max. working pressure 15 bar*
- *Min/max. working temperature 0°C / +90°C*
- *Nickel plated brass head and ring*
- *1/2", 3/4", 1" heads have M6 hole for cartridge stay-rod*
- *Possibility to equip with pressure gauge*
- *Pressure release screw*
- *The models having 1/2" - 3/4" - 1" connections can be equipped with wall bracket*

** Heads with 1" 1/4, 1" 1/2, 2" connections require cartridges series GTS*

CONTENITORE INOX AD USO INDUSTRIALE DOVE É NECESSARIO GARANTIRE UN'ELEVATA RESISTENZA MECCANICA E AFFIDABILITÀ NEGLI IMPIEGHI CON ALTE TEMPERATURE.

STAINLESS STEEL HOUSING FOR INDUSTRIAL APPLICATIONS WHICH REQUIRE STRONG MECHANICAL RESISTANCE AND USE WITH HIGH TEMPERATURES.

VASO IN ACCIAO INOX AISI 304 / *AISI 304 STAINLESS STEEL BOWL*


CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6050380	1/2"	5"	135 - 185	6	12	36	3,00	0,064
0A6070380	1/2"	7"	135 - 235	6	6	22	3,67	0,064
0A6090380	1/2"	9 3/4"	135 - 337	6	6	25	4,17	0,064
0A6050480	3/4"	5"	135 - 185	6	12	36	3,00	0,064
0A6070480	3/4"	7"	135 - 235	6	6	22	3,67	0,064
0A6090480	3/4"	9 3/4"	135 - 337	6	6	18	3,00	0,064
0A6200480	3/4"	20"	135 - 565	6	6	25	4,17	0,11
0A6050580	1"	5"	135 - 185	6300	12	36	3,00	0,064
0A6070580	1"	7"	135 - 235	6300	6	22	3,67	0,064
0A6090580	1"	9 3/4"	135 - 337	6300	6	18	3,00	0,064
0A6200580	1"	20"	135 - 565	6300	6	25	4,17	0,11
0A6100680	1 1/4" *	9 3/4"	150 - 355	12000	6	21	3,50	0,064
0A6200680	1 1/4" *	20"	150 - 587	12000	6	27	4,50	0,11
0A6100780	1 1/2" *	9 3/4"	150 - 355	13000	6	20	3,33	0,064
0A6200780	1 1/2" *	20"	150 - 587	13000	6	26	4,33	0,11
0A6100880	2" *	9 3/4"	162 - 363	14000	6	25	4,17	0,064
0A6200880	2" *	20"	162 - 595	14000	6	31	5,17	0,11



SX600 sc

VASO IN ACCIAIO INOX AISI304 CON SCARICO FILETTATO.
AISI 304 STAINLESS STEEL BOWL WITH Thread WASTE DISCHARGE OUTLET 1/2"

CODICE	ATTACCHI	LUNGH. CART.	DIM. L - H MM	PORTATA LT/ORA	PEZZI PER CONF.	PESO MASTER (KG)	PESO UNITÁ (KG)	VOL. M3
CODE	*CONNECT.*	*CARTR. LENGHT*	*DIM. L - H MM*	*FLOW RATE LT/H*	*PCS/BOX*	*MASTER BOX WEIGHT (KG)*	*UNIT WEIGHT (KG)*	*VOL. M3*
0A6050381	1/2"	5"	135 - 185	6	12	36	3,00	0,064
0A6070381	1/2"	7"	135 - 235	6	6	22	3,67	0,064
0A6090381	1/2"	9 3/4"	135 - 337	6	6	25	4,17	0,064
0A6050481	3/4"	5"	135 - 185	6	12	36	3,00	0,064
0A6070481	3/4"	7"	135 - 235	6	6	22	3,67	0,064
0A6090481	3/4"	9 3/4"	135 - 337	6	6	18	3,00	0,064
0A6200481	3/4"	20"	135 - 565	6	6	25	4,17	0,11
0A6050581	1"	5"	135 - 185	6300	12	36	3,00	0,064
0A6070581	1"	7"	135 - 235	6300	6	22	3,67	0,064
0A6090581	1"	9 3/4"	135 - 235	6300	6	18	3,00	0,064
0A6200581	1"	20"	135 - 337	6300	6	25	4,17	0,11
0A6100681	1 1/4" *	9 3/4"	150 - 355	12000	6	21	3,50	0,064
0A6200681	1 1/4" *	20"	150 - 587	12000	6	27	4,50	0,11
0A6100781	1 1/2" *	9 3/4"	150 - 355	13000	6	20	3,33	0,064
0A6200781	1 1/2" *	20"	150 - 587	13000	6	26	4,33	0,11
0A6100881	2" *	9 3/4"	162 - 363	14000	6	25	4,17	0,064
0A6200881	2" *	20"	162 - 595	14000	6	31	5,17	0,11



MASTER BOX	CONFEZIONE / *PACKAGING*
7" - 9 3/4" = 6 pz. unit. 40*40*40 (cm)	1 pz. unit. 13*37*18 (cm)
20" = 6 pz. unit. 51*62*40 (cm)	1 pz. unit. 18*60*15 (cm)
5" = 24 pz. unit. 44*57*44 (cm)	1pz. unit. 14*14*21 (cm)

***CARTUCCE CONSIGLIATE**
RECOMMENDED CARTRIDGES
SX600: FPP/X/FA/GT/XP/GTX /GTS */GTSX */XSM *
PAG./PG.63 / 70 / 60 / 64 / 70 / 67 / 71
SX600 sc: GT/AP/XM/AP/GTX/AP /GTS/AP * /GTSX/AP */XSM *
PAG./PG.64 / 71 / 67 / 71

ISTRUZIONI PER L'USO
E LA MANUTENZIONE DEI FILTRI

Instructions for the use and maintenance of the filters


ISTRUZIONI GENERALI PER L'INSTALLAZIONE, L'USO E LA MANUTENZIONE

- I contenitori per cartucce riportati in questo catalogo devono essere utilizzati solamente per le applicazioni indicate dal costruttore. In caso di utilizzo diverso non autorizzato, si declina ogni responsabilità.
- L'utilizzo di tutti i contenitori portacartucce deve tenere conto dei limiti di pressione d'esercizio fissati nel presente catalogo.
- I contenitori portacartucce costruiti con vaso in SAN trasparente sono idonei a trattare liquidi di pH neutro. Per trattamento di liquidi con pH aggressivi si scelgano i contenitori più adatti secondo le indicazioni riportate nel presente catalogo.
- I contenitori portacartucce in plastica non devono essere né installati né immagazzinati in ambienti esposti al sole o al gelo. I raggi ultravioletti, le alte temperature così come le temperature molto basse, possono limitare la durata dell'apparecchio o pregiudicarne l'integrità sino alla rottura.
- Se si prevede un utilizzo con contenitore esposto alla luce si consiglia di usare contenitori con vaso bianco.
- Per fissare i contenitori al muro, usare gli appositi supporti (vedi accessori). Usare raccordi flessibili con filettatura cilindrica a passo gas (fig.B). Non usare raccordi conici né tubature filettate direttamente sul contenitore (fig.C).
- Nell'effettuare l'operazione di montaggio prevedere uno spazio operativo (fig.A) ed un BY-PASS che permetta di isolare l'impianto durante la manutenzione o sostituzione (fig.B).
- Nella fase di montaggio non utilizzare paste sigillanti, siliconi o canapa ma solo TEFLON (fig.D).


GENERAL INSTRUCTIONS FOR USE, MAINTENANCE AND INSTALLATION

- The filter housings shown in this catalogue may be used only for the purposes indicated by the manufacturer. AMG Srl doesn't assume any liability in case of not authorized different utilisation.
- All filter housings may be used only within the limit of the relative working pressures and temperatures stated in this catalogue.
- The filter housings equipped with transparent SAN bowls are suitable for the treatment of liquids with neutral pH. For liquids with aggressive pH please choose the most appropriated filter housing as per indications given in this catalogue.
- Plastic filter housings may neither be installed nor stored in places exposed to sunlight and/or freezing temperatures. Ultra-violet rays as well as high and very low temperatures may not only limit the lifetime of the appliance but even, compromise its integrity up to breakage.
- If the filter housing has to be installed in a place exposed to light it is advisable to choose an opaque housing.
- For fixing the unit to the wall the appropriated wall brackets should be used (see accessories). For installation of the filter housing use flexible hoses with gas cylindrical thread (fig.B). Do not use conical thread fittings or thread hoses directly onto the filter housing (fig.C).
- When installing the filter housing an operational space must be left (fig.A). Furthermore a BY-PASS system should be installed allowing to disconnect the filter from the water supply net during maintenance or replacement operations (fig.B).
- For mounting of the unit do not use sealant pastes, silicone or hemp but only TEFLON (fig.D).


(Fig.A)




(Fig.B)



(Fig.C)



(Fig.D)



MANUTENZIONE

- Accertarsi accuratamente che il contenitore prima di essere usato sia perfettamente avvitato. Altrimenti possono verificarsi perdite d'acqua e allagamenti.
- Per la pulizia dei contenitori usare esclusivamente spugne e acqua corrente. Evitare l'uso di alcool, solventi e detergenti. La pulizia va effettuata almeno ogni volta che si sostituisce la cartuccia filtrante.
- In caso di caduta del contenitore durante l'operazione di manutenzione o pulizia, si consiglia di effettuare la sostituzione del contenitore stesso in quanto potrebbero essere avvenute delle micro rotture che, anche se non visibili, potrebbero causare la rottura completa del contenitore.

SOSTITUZIONE DELLA CARTUCCIA

- Chiudere il flusso dell'acqua o, se é stato installato un By-pass, isolare il contenitore.
- Togliere la pressione dell'apparecchio svitando la valvolina di sfiato, poi svitare l'apparecchio usando l'apposita chiave.
- Dopo aver tolto la cartuccia usata, pulire il contenitore e quindi effettuare la sostituzione della cartuccia.
- Prima di riavvitare il vaso alla testata, assicurarsi che l'O-Ring sia ben posizionato e quindi riaprire il flusso dell'acqua lasciando aperta la valvolina di sfiato sino alla fuoriuscita di tutta l'aria dal contenitore.
- Lasciare scorrere l'acqua per alcuni minuti prima di utilizzarla.
- Si consiglia la sostituzione della cartuccia filtrante ogni 6 mesi o comunque entro 12 mesi.

GARANZIA

Tutti gli articoli prodotti dalla ditta AMG Srl sono coperti da garanzia di 12 mesi dalla data d'acquisto alle seguenti condizioni:

- Gli articoli devono essere installati ed utilizzati secondo le norme del costruttore.
- Le operazioni di manutenzione vengono periodicamente effettuate secondo le norme del costruttore.
- La garanzia é limitata alla sola sostituzione della parte difettosa escludendo qualsiasi altro diritto di risarcimento per danni diretti o indiretti causati dal prodotto stesso.
- La sostituzione in garanzia verrà effettuata solamente dopo la resa del prodotto ritenuto difettoso e dopo che questo é stato esaminato dai tecnici AMG per accertarne la difettosità e stabilirne le cause.
- Le spese di trasporto e di manodopera per la sostituzione del pezzo in garanzia, sono a carico dell'acquirente.
- La mancata osservanza delle norme generali per l'installazione, uso e manutenzione sopra indicate, così come il non rispetto delle Leggi Italiane ed Europee inerenti, fanno decadere ogni garanzia sui prodotti AMG.

CONDIZIONI GENERALI DI VENDITA

- AMG Srl accetta solamente ordini pervenuti per iscritto e si riserva il diritto di confermare o meno questi ordini.
- Le merci sono vendute Franco Stabilimento AMG.
- In mancanza di istruzioni particolari AMG provvederà a spedire la merce a sua discrezione.
- AMG Srl declina ogni responsabilità dal momento in cui le merci escono dal suo magazzino.
- AMG Srl si riserva il diritto di apportare modifiche ai propri prodotti ed ai prezzi senza alcun preavviso.
- Per qualunque controversia si applicherà la legge italiana ed il foro competente sarà quello di REGGIO EMILIA.

AMG Srl si riserva il diritto di apportare modifiche senza preavviso

MAINTENANCE

- Before using the filter make sure that the filter housing is perfectly screwed, otherwise water will leak and may cause flooding.
- For cleaning the housing only use a sponge and running water. Do not use alcohol, solvents or detergents. The housing must be cleaned at least every time you replace the filter cartridge.
- If the bowl should drop on the floor during the maintenance operations it must be replaced as this could cause some breakages which, even though they might be invisible to the naked eye, can lead to breakage of the bowl.

REPLACING OF FILTERING CARTRIDGES

- Turn off the water flow or, if a BY-PASS system has been installed, disconnect the filter housing.
- Release the pressure from the housing by loosening the air valve, then unscrew the bowl by means of its proper wrench.
- Remove the used cartridge, clean the filter housing and replace the cartridge.
- Before screwing the bowl to the head, make sure that the O-Ring and the cartridge are correctly positioned.
  Turn on the water flow and leave the air valve open until the air has completely escaped from the filter housing.
- Leave the water running for a few minutes before reusing it.
- We suggest the replacement of the filter cartridge every 6 months, anyhow within 12 months

WARRANTY

All items manufactured by AMG Srl are covered by 12 months warrantee from date of purchase under the following conditions:

- All items must be installed and used according to the manufacturer's instructions.
- Maintenance operations must be carried out following the manufacturer's instructions.
- Warrantee is limited to the only replacement of defective parts excluding any other claims by the customer for direct or indirect damages caused by the product.
- Replacement under warrantee will be made only after returning of the product supposed to be faulty to the manufacturer and after examination of the same by AMG technicians, in order to check the faultiness and to ascertain the causes.
- Costs for transport and labour relating to the replacement of parts covered by warrantee are at charge of the buyer.
- No warrantee claims will be accepted on AMG products if the defectiveness derives from non-observance of the rules stated under "GENERAL INSTRUCTIONS FOR USE, MAINTENANCE AND INSTALLATION" and/or non-compliance with the relevant Italian and European laws.

GENERAL SALES CONDITIONS

- AMG Srl accepts only written orders and reserves the right to confirm these or not.
- All goods are sold "EX WORKS AMG".
- Without any particular instructions from side of the customer, AMG Srl will dispatch the goods at its discretion.
- AMG Srl refuses any liability from the moment in which the goods have left its warehouse.
- AMG Srl reserves the right to modify its products and prices without prior notice.
- For any dispute the applicable law will be the Italian law and place of jurisdiction will be REGGIO EMILIA.

AMG Srl reserves the right to carry out modifications on its products without prior notice