

TUBO SPIRALATO PER USO CIVILE E INDUSTRIALE, IN PVC RIGIDO ANTIURTO, COMPLETO DI KIT DRENAGGIO.
HELICALLY WOUND PIPE FOR DOMESTIC AND INDUSTRIAL USES, IN RIGID PLASTICIZED SHOCKPROOF PVC,
COMPLETE WITH DRAINAGE KIT.



TD



CARATTERISTICHE TECNICHE

- Pressione max d'esercizio: 6 bar
- Temperatura min/max d'esercizio: -5°C / +60°C
- Spirale in PVC rigida antiurto colore nero/trasparente, spessore 2 mm.
- Completo di:
 - Terminale 1" M
 - Terminale 1" F girevole
- Fornito con kit d'installazione con nipples 1" e 1" 1/4 sia M che F

TECHNICAL FEATURES

- *Max working pressure: 6 bar*
- *Min/max working temperature: -5°C / +60°C*
- *Rigid shockproof PVC spiral, black/transparent color, thickness 2 mm.*
- *Complete with:*
 - *Fitting 1" M*
 - *Swivelling fitting 1" F*
- *Provided with installation kit with nipple 1" and 1" 1/4 both M and F*

CODICE	MODELLO	LUNGHEZZA TUBO	DIMENSIONI MATASSA	KG PER CONFEZIONE
CODE	MODEL	HOSE LENGHT	PACKAGING DIMENSIONS	KG PER PACKING
1TD040001	TD 4	4 m	32 - 9	0,68
1TD070001	TD 7	7 m	35 - 11	1,19
1TD100001	TD 10	10 m	37 - 13	1,7